

ASTM F436
Standard Specification for Hardened Steel Washers

単位は、in.をmm換算しております

呼び寸法	外径 OD	内径 I.D.	板厚 T
1/4	15.07 ~ 16.68	7.14 ~ 7.95	1.30 ~ 2.03
5/16	16.67 ~ 18.28	8.74 ~ 9.55	1.30 ~ 2.03
3/8	19.84 ~ 21.46	10.32 ~ 11.12	1.30 ~ 2.03
7/16	22.61 ~ 24.23	11.92 ~ 12.72	1.30 ~ 2.03
1/2	26.19 ~ 27.81	13.49 ~ 14.30	2.47 ~ 4.49
9/16	29.37 ~ 30.98	15.88 ~ 16.68	2.80 ~ 4.49
5/8	32.55 ~ 34.13	17.48 ~ 18.28	3.10 ~ 4.49
3/4	36.48 ~ 38.10	20.66 ~ 21.46	3.10 ~ 4.49
7/8	43.64 ~ 45.26	23.83 ~ 24.63	3.46 ~ 4.49
1	49.20 ~ 52.40	27.01 ~ 28.60	3.46 ~ 4.49
1 1/8	55.55 ~ 58.75	30.18 ~ 31.77	3.46 ~ 4.49
1 1/4	61.90 ~ 65.10	34.93 ~ 36.52	3.46 ~ 4.49
1 3/8	68.25 ~ 71.45	38.10 ~ 39.70	3.46 ~ 4.49
1 1/2	74.60 ~ 77.80	41.28 ~ 42.87	3.46 ~ 4.49
1 3/4	84.13 ~ 87.32	47.63 ~ 49.22	4.53 ~ 7.11
2	93.65 ~ 96.85	53.98 ~ 55.57	4.53 ~ 7.11
2 1/4	100.00 ~ 103.20	60.33 ~ 61.92	6.10 ~ 8.63
2 1/2	112.70 ~ 115.90	66.68 ~ 68.27	6.10 ~ 8.63

ASTM F436M
Standard Specification for Hardened Steel Washers

単位は、in.をmm換算しております

呼び寸法	外径 OD	内径 I.D.	板厚 T
12	25.7 ~ 27.0	14.0 ~ 14.4	3.1 ~ 4.6
16	32.4 ~ 34.0	18.0 ~ 18.4	3.1 ~ 4.6
20	40.4 ~ 42.0	22.0 ~ 22.5	3.1 ~ 4.6
22	42.4 ~ 44.0	24.0 ~ 24.5	3.4 ~ 4.6
24	48.4 ~ 50.0	26.0 ~ 26.5	3.4 ~ 4.6
27	54.1 ~ 56.0	30.0 ~ 30.5	3.4 ~ 4.6
30	58.1 ~ 60.0	33.0 ~ 33.6	3.4 ~ 4.6
36	70.1 ~ 72.0	39.0 ~ 39.6	3.4 ~ 4.6
42	81.8 ~ 84.0	45.0 ~ 45.6	4.6 ~ 7.2
48	92.8 ~ 95.0	52.0 ~ 52.7	4.6 ~ 7.2